
FnIO G-Series

GT-3914, GT-3924

GT-3914 (4 Channels, Differential Current Input, 0~20mA / 4~20mA / -20~20mA, 12bits)

GT-3924 (4 Channels, Differential Voltage Input, 0~10V / 0~5V / -10~10V / -5~5V, 12bits)

Specification

History

REV.	PAGES	REMARKS	DATE	Editor
1.00	16		Oct. 25, 2016	Kim,Hongseok
1.01		Specification(GT-3914)	Jan. 09, 2017	Kim, Hongseok

Specification

History.....	2
Table of Contents.....	3
1.Environment Specification.....	4
2.GT-3914(4 Channels, Differential Current Input, 0~20mA / 4~20mA / -20~20mA, 12bits).....	5
2.1.GT-3914Specification	5
2.2.GT-3914Wiring Diagram.....	6
2.3.GT-3914LED Indicator.....	7
2.3.1.LED Indicator.....	7
2.3.2.Channel Status LED.....	7
2.4.Data Value / Current	8
2.5.Mapping Data into the Image Table.....	9
3.GT-3924(4 Channels, Differential Voltage Input, 0~10V / 0~5V / -10~10V / -5~5V, 12bits).....	10
3.1.GT-3924Specification	10
3.2.GT-3924Wiring Diagram.....	11
3.3.GT-3924LED Indicator.....	12
3.3.1.LED Indicator.....	12
3.3.2.Channel Status LED.....	12
3.4.Data Value / Voltage.....	13
3.5.Mapping Data into the Image Table.....	15
4.Input Range Setting & Conversion Time Setting.....	16
4.1.GT-3914.....	16
4.2.GT-3924.....	16

Specification

1. Environment Specification

Environmental Specification	
Operation Temperature	-40°C ~ 60°C
UL Temperature	-20°C ~ 60°C
Non-Operating Temperature	-40°C ~ 85°C
Relative Humidity	5% ~ 90% Non-condensing
Mounting	DIN rail
General Specification	
Shock Operating	IEC 60068-2-27
Vibration Resistance	Based on IEC 60068-2-6 Sine Vibration <ul style="list-style-type: none"> - 5 ~ 25Hz : $\pm 1.6\text{mm}$ - 25 ~ 300Hz : 4g - Sweep Rate : 1 Oct/min, 20 cycles Random Vibration <ul style="list-style-type: none"> - 10 ~ 40 Hz : $0.0125 \text{ g}^2/\text{Hz}$ - 40 ~ 100 Hz : $0.0125 \rightarrow 0.002 \text{ g}^2/\text{Hz}$ - 100 ~ 500 Hz : $0.002 \text{ g}^2/\text{Hz}$ - 500 ~ 2000 Hz : $0.002 \rightarrow 1.3 \times 10^{-4} \text{ g}^2/\text{Hz}$ - Test time : 1hrs for each test
Industrial Emissions	EN61000-6-4/All : 2011
Industrial Immunity	EN 61000-6-2 : 2005
Installation Position	Vertical and horizontal installation is available
Product Certifications	CE, UL

Specification


2. GT-3914 (4 Channels, Differential Current Input, 0~20mA / 4~20mA / -20~20mA, 12bits)

2.1. GT-3914 Specification

Items	Specification
Input Specification	
Inputs Per Module	4 Channels Differential, Non-isolated Between Channels
Indicators	4 Green Input Status LEDs
Resolution in Ranges	12 bits : 4.88uA/bit(0~20mA) 12 bits : 3.91uA/bit(4~20mA) 12 bits : 9.77uA/bit(-20~20mA)
Input Range	0~20mA, 4~20mA, -20~20mA
Data Format	16bits Integer (2' compliment)
Module Error	±0.1% Full Scale @ 25°C ±0.3% Full Scale @ -40°C, 60°C
Input Impedance	121.5Ω
Diagnostic	Field Power Off : LED Blinking Field Power On : LED Off < 0.5% (Maximum Input Value) Field Power On : LED On > 0.5% (Maximum Input Value)
Conversion Time	1msec / All channel
Calibration	Not Required
Common Type	1 Common, Field Power 0V is Common(AGND)
General Specification	
Power Dissipation	Max. 30mA @ 5Vdc
Isolation	I/O to Logic : Photocoupler Isolation Field power : DC/DC Converter Isolation
Field Power	Supply Voltage : 24Vdc nominal Voltage Range : 60°C : 18 ~ 26.4Vdc 50°C : 18 ~ 32Vdc Power Dissipation : Max. 40mA@24Vdc
Wiring	I/O Cable Max. 2.0mm ² (AWG 14)
Weight	58g
Module Size	12mm x 99mm x 70mm
Environment Condition	Refer to 'Environment Specification'

Specification

2.2. GT-3914 Wiring Diagram



Pin No.	Signal Description	Signal Description	Pin No.
0	Input Channel 0(+)	Input Channel 0(-)	1
2	Input Channel 1(+)	Input Channel 1(-)	3
4	Input Channel 2(+)	Input Channel 2(-)	5
6	Input Channel 3(+)	Input Channel 3(-)	7
8	Input Channel Common(AGND)	Field Ground	9

Specification

2.3. GT-3914 LED Indicator

2.3.1. LED Indicator



LED No.	LED Function / Description	LED Color
0	INPUT Channel 0	Green
1	INPUT Channel 1	Green
2	INPUT Channel 2	Green
3	INPUT Channel 3	Green

2.3.2. Channel Status LED


Status	LED	To indicate
Normal Operation	[LED Off < 0.5% (Maximum Input Value)] - Channel OFF [LED On > 0.5% (Maximum Input Value)] - Channel Green	Normal Operation
Normal Operation	0~20mA : LED Off > 21mA, LED Off < 0mA 4~20mA : LED Off > 21mA, LED Off < 3mA -20~20mA : LED Off > 21mA, LED Off < -21mA	Over range Check
Field Power Error	All Channel Repeat the Green and OFF	Field Power is unconnected

Specification

2.4. Data Value / Current


Current Range : 0~20mA

Current	0.0mA	5.0mA	10.0mA	20.0mA
Data(Hex)	H0000	H03FF	H07FF	H0FFF



Current Range : 4~20mA


Current	4.0mA	8.0mA	12.0mA	20.0mA
Data(Hex)	H0000	H03FF	H07FF	H0FFF



Specification

Current Range : -20~20mA


Current	-20.0mA	-10.0mA	0mA	+10.0mA	+20.mA
Data(Hex)	HF800	HFC00	H0000	H03FF	H07FF



2.5. Mapping Data into the Image Table

● Input Module Data

Analog Input Ch0
Analog Input Ch1
Analog Input Ch2
Analog Input Ch3



● Input Image Value

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte 0	Analog Input Ch0 Low byte							
Byte 1	Analog Input Ch0 High byte							
Byte 2	Analog Input Ch1 Low byte							
Byte 3	Analog Input Ch1 High byte							
Byte 4	Analog Input Ch2 Low byte							
Byte 5	Analog Input Ch2 High byte							
Byte 6	Analog Input Ch3 Low byte							
Byte 7	Analog Input Ch3 High byte							

Specification


3. GT-3924 (4 Channels, Differential Voltage Input, 0~10V / 0~5V / -10~10V / -5~5V, 12bits)

3.1. GT-3924 Specification

Items	Specification
Input Specification	
Inputs Per Module	4 Channels Differential, Non-isolated Between Channels
Indicators	4 Green Input Status LEDs
Resolution in Ranges	12 bits : 2.44mV/Bit(0~10V) 12 bits : 1.22mV/Bit(0~5V) 12 bits : 4.88mV/Bit(-10~10V) 12 bits : 2.44mV/Bit(-5~5V)
Input Range	0~10Vdc, 0~5Vdc, -10~10Vdc, -5~5Vdc
Data Format	16bits Integer (2' compliment)
Module Error	±0.1% Full Scale @ 25°C ±0.3% Full Scale @ -40°C, 60°C
Input Impedance	667kΩ
Diagnostic	Diagnostic Field Power Off : LED Blinking Field Power On : LED Off < 0.5% (Maximum Input Value) Field Power On : LED On > 0.5% (Maximum Input Value)
Conversion Time	1msec / All channel (≤ 0.25ms per channel)
Calibration	Not Required
Common Type	1 Common, Field Power 0V is Common(AGND)
General Specification	
Power Dissipation	Max. 30mA @ 5Vdc
Isolation	I/O to Logic : Photocoupler Isolation Field power : Non-Isolation
Field Power	Supply Voltage : 24Vdc nominal Voltage Range : 18 ~ 32Vdc Power Dissipation : Max. 45mA@24Vdc
Wiring	I/O Cable Max. 2.0mm ² (AWG 14)
Weight	58g
Module Size	12mm x 99mm x 70mm
Environment Condition	Refer to 'Environment Specification'

Specification

3.2. GT-3924 Wiring Diagram



Pin No.	Signal Description	Signal Description	Pin No.
0	Input Channel 0(+)	Input Channel 0(-)	1
2	Input Channel 1(+)	Input Channel 1(-)	3
4	Input Channel 2(+)	Input Channel 2(-)	5
6	Input Channel 3(+)	Input Channel 3(-)	7
8	Input Channel Common(AGND)	Field Ground	9

Specification

3.3. GT-3924 LED Indicator

3.3.1. LED Indicator



LED No.	LED Function / Description	LED Color
0	INPUT Channel 0	Green
1	INPUT Channel 1	Green
2	INPUT Channel 2	Green
3	INPUT Channel 3	Green


3.3.2. Channel Status LED

Status	LED	To indicate
Normal Operation	[LED Off < 0.5% (Maximum Input Value)] - Channel OFF [LED On > 0.5% (Maximum Input Value)] - Channel Green	Normal Operation
Field Power Error	All Channel Repeat the Green and OFF	Field Power is unconnected

3.4. Data Value / Voltage


Voltage Range : 0~10V

Voltage	0V	2.5V	5.0V	10.0V
Data(Hex)	H0000	H03FF	H07FF	H0FFF



Voltage Range : 0~5V


Current	0V	1.25V	2.5V	5.0V
Data(Hex)	H0000	H03FF	H07FF	H0FFF



Specification


Voltage Range : -10~10V

Current	-10V	-5V	0V	5.0V	10.0V
Data(Hex)	HF800	HFC00	H0000	H03FF	H07FF



Voltage Range : -5~5V


Current	-5V	-2.5V	0V	2.5V	5.0V
Data(Hex)	HF800	HFC00	H0000	H03FF	H07FF



3.5. Mapping Data into the Image Table

● Input Module Data

Analog Input Ch0
Analog Input Ch1
Analog Input Ch2
Analog Input Ch3



● Input Image Value

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte 0	Analog Input Ch0 Low byte							
Byte 1	Analog Input Ch0 High byte							
Byte 2	Analog Input Ch1 Low byte							
Byte 3	Analog Input Ch1 High byte							
Byte 4	Analog Input Ch2 Low byte							
Byte 5	Analog Input Ch2 High byte							
Byte 6	Analog Input Ch3 Low byte							
Byte 7	Analog Input Ch3 High byte							

Specification

4. Input Range Setting & Conversion Time Setting

4.1. GT-3914

Byte	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
0	Ch#0 Command(H00 : 0~20mA, H01 : 4~20mA, H02 : -20~20mA)							
1	Ch#1 Command(H00 : 0~20mA, H01 : 4~20mA, H02 : -20~20mA)							
2	Ch#2 Command(H00 : 0~20mA, H01 : 4~20mA, H02 : -20~20mA)							
3	Ch#3 Command(H00 : 0~20mA, H01 : 4~20mA, H02 : -20~20mA)							
4	Filter Time(H00 : Default Filter(=20), H01 : Fastest ~ H62 : Slowest)							
5	Reserve							

* ID_PARAMETER (6Byte)

4.2. GT-3924

Byte	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
0	Ch#0 Command(H00 : 0~10V, H01 : 0~5V, H02 : -10~10V, H03 : -5~5V)							
1	Ch#1 Command(H00 : 0~10V, H01 : 0~5V, H02 : -10~10V, H03 : -5~5V)							
2	Ch#2 Command(H00 : 0~10V, H01 : 0~5V, H02 : -10~10V, H03 : -5~5V)							
3	Ch#3 Command(H00 : 0~10V, H01 : 0~5V, H02 : -10~10V, H03 : -5~5V)							
4	Filter Time(H00 : Default Filter(=20), H01 : Fastest ~ H62 : Slowest)							
5	Reserve							

* ID_PARAMETER (6Byte)